

## 1 Identification

- **Product identifier**
- **Trade name:** 50101 & 50104 World Class Acrylic Surfacer
- **Article number:** 50101, 50104
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225      Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315      Causes skin irritation.

Eye Irrit. 2A H319      Causes serious eye irritation.

STOT SE 3 H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02      GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

Talc

4-chloro-alpha,alpha,alpha-trifluorotoluene

2,6-dimethylheptan-4-one

- **Hazard statements**

H225      Highly flammable liquid and vapor.

H315      Causes skin irritation.

H319      Causes serious eye irritation.

(Contd. on page 2)

**Trade name: 50101 & 50104 World Class Acrylic Surfacer**

(Contd. of page 1)

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



**HMIS-ratings (scale 0 - 4)**



**Other hazards**

**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

**Description:**

Mixture: consisting of the following components.  
Weight percentages

(Contd. on page 3)



Trade name: 50101 & 50104 World Class Acrylic Surfacer

(Contd. of page 2)

· <b>Dangerous components:</b>		
67-64-1	acetone	30-40%
14807-96-6	Talc	13-30%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	≥7-<10%
540-88-5	tert-butyl acetate	≥7-<10%
108-83-8	2,6-dimethylheptan-4-one	1.5-5%
108-65-6	2-methoxy-1-methylethyl acetate	1.5-5%
	DISPARLON 6000 LOT	1.5-5%
19549-80-5	4,6-dimethylheptan-2-one	1-1.5%

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

(Contd. on page 4)



Trade name: 50101 & 50104 World Class Acrylic Surfacers

(Contd. of page 3)

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
540-88-5	tert-butyl acetate	600 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
108-83-8	2,6-dimethylheptan-4-one	75 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm

· **PAC-2:**

67-64-1	acetone	3200* ppm
540-88-5	tert-butyl acetate	1,700 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
108-83-8	2,6-dimethylheptan-4-one	330 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm

· **PAC-3:**

67-64-1	acetone	5700* ppm
540-88-5	tert-butyl acetate	10,000 ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm

**7 Handling and storage**

· **Handling:**

· **Precautions for safe handling** No special measures required.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)



Trade name: 50101 & 50104 World Class Acrylic Surfacer

(Contd. of page 4)

· **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**67-64-1 acetone**

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
BEI	

**540-88-5 tert-butyl acetate**

PEL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**108-83-8 2,6-dimethylheptan-4-one**

PEL	Long-term value: 290 mg/m <sup>3</sup> , 50 ppm
REL	Long-term value: 150 mg/m <sup>3</sup> , 25 ppm
TLV	Long-term value: 145 mg/m <sup>3</sup> , 25 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Trade name: 50101 & 50104 World Class Acrylic Surfacer

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	According to product specification
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	55 °C

· **Flash point:** -18 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 465 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

· <b>Lower:</b>	2.6 Vol %
· <b>Upper:</b>	13 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 1.17385 g/cm<sup>3</sup>

· **Relative density** Not determined.

(Contd. on page 7)



Trade name: 50101 & 50104 World Class Acrylic Surfacers

(Contd. of page 6)

- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 54.2 %
  - VOC content:** 5.78 %
  - 145.8 g/l / 1.22 lb/gl
- **Solids content:** 44.0 %
- **Other information** No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 8)



Trade name: 50101 & 50104 World Class Acrylic Surfacer

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1263

· **UN proper shipping name**

· **DOT** Paint

· **ADR** 1263 Paint, special provision 640D

· **IMDG, IATA** PAINT

(Contd. on page 9)



Trade name: 50101 & 50104 World Class Acrylic Surfacers

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· **ADR**  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **IMDG**  
· **Limited quantities (LQ)** 1L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II



Trade name: 50101 & 50104 World Class Acrylic Surfacers

(Contd. of page 9)

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

14807-96-6	Talc
	Acrylic Resin
1330-20-7	xylene
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
14807-96-6	Talc
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
540-88-5	tert-butyl acetate
13463-67-7	titanium dioxide
108-83-8	2,6-dimethylheptan-4-one
108-65-6	2-methoxy-1-methylethyl acetate
19549-80-5	4,6-dimethylheptan-2-one
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· TSCA new (21st Century Act) (Substances not listed)

DISPARLON 6000 LOT

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
1330-20-7	xylene	I

(Contd. on page 11)

Trade name: 50101 & 50104 World Class Acrylic Surfacers

(Contd. of page 10)

100-41-4	ethylbenzene	D
<b>· TLV (Threshold Limit Value established by ACGIH)</b>		
67-64-1	acetone	A4
14807-96-6	Talc	A4
13463-67-7	titanium dioxide	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

<b>· NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

Talc

4-chloro-alpha,alpha,alpha-trifluorotoluene

2,6-dimethylheptan-4-one

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

(Contd. on page 12)

**Trade name: 50101 & 50104 World Class Acrylic Surfacer**

(Contd. of page 11)

- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*
- P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235 *Store in a well-ventilated place. Keep cool.*
- P405 *Store locked up.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Rita Joiner (rjoiner@semproducts.com)
- **Date of preparation / last revision** 03/14/2018 / 8
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flam. Liq. 2: Flammable liquids – Category 2
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**